OMB 3067-0077

## **ELEVATION GERTIFICATE** (

## FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR).

Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION FOR INSURANCE COMPANY USE BUILDING OWNER'S NAME POLICY NUMBER Normandy Village, Inc. STREET ADDRESS(Including Apt., Unit, Suite and/or Bldg.Number)OR P.O.ROUTE AND BOX NUMBER COMPANY NAIC NUMBER 3730 Fairfield Avenue OTHER DESCRIPTION (Lot and Block Numbers, etc.) Building 26, Normandy Village STATE ZIP CODE CITY Louisiana 71104 Shreveport, SECTION B FLOOD INSURANCE RATE MAP (FIRM) INFORMATION Provide the following from the proper FIRM (See Instructions): 1. COMMUNITY NUMBER 4. DATE OF FIRM INDEX 6. BASE FLOOD ELEVATION 2. PANEL NUMBER 3. SUFFIX 5. FIRM ZONE (in AO Zones, use depth) 178.00 April 17, 1995 220036 0025  $\mathbf{C}$ A-E 7. Indicate the elevation datum system used on the FIRM for Base Flood Elevations(BFE): NGVD'29 Other (describe on back) 8. For Zones A or V, where no BFE is provided on the FIRM, and the community has established a BFE for this building site, indicate the community's feet NGVD (or other FIRM datum-see Section B, Item 7). SECTION C BUILDING ELEVATION INFORMATION 1. Using the Elevation Certificate Instructions, indicate the diagram number from the diagrams found on Pages 5 and 6 that best describes the subject building's reference level 2 (a), FIRM Zones Al-A30, AE, AH, and A (with BFE). The top of the reference level floor from the selected diagram is at an elevation of 175.03 feet NGVD (or other FIRM datum-see Section B, Item 7). (b), FIRM Zones V1-V30, VE, and V (with BFE). The bottom of the lowest horizontal structural member of the reference level from the selected \_ feet NGVD (or other FIRM datum-see Section B, Item 7). diagram is at an elevation of feet above or below (check one) the (c). FIRM Zone A (without BFE). The floor used as the reference level from the selected diagram is \_ highest grade adjacent to the building. (d), FIRM Zone AO. The floor used as the reference level from the selected diagram is \_\_\_ feet above \_\_\_ or below \_\_ (check one) the highest grade adjacent to the building. If no flood depth number is available, is the building's lowest floor (reference level) elevated in accordance with the community's floodplain management ordinance? Yes No Unknown 3. Indicate the elevation datum system used in determining the above reference level elevations: NGVD '29 Other (describe under Comments on Page 2). (NOTE: If the elevation datum used in measuring the elevations is different than that used on the FIRM [see Section 8, Item 7], then convert the elevations to the datum system used on the FIRM and show the conversion equation under Comments on Page 2.) 4. Elevation reference mark used appears on FIRM: Yes X No (See Instructions on Page 4) actual construction L construction drawings 5. The reference level elevation is based on: (NOTE: Use of construction drawings is only valid if the building does not yet have the reference level floor in place, in which case this certificate will only be valid for the building during the course of construction. A post-construction Elevation Certificate will be required once construction is complete.) 174.65 6. The elevation of the lowest grade immediately adjacent to the building is: feet NGVD (or other FIRM datum see Section B, Item 7). SECTION D COMMUNITY INFORMATION 1. If the community official responsible for verifying building elevations specifies that the reference level indicated in Section C, Item 1 is not the "lowest floor" as defined in the community's floodplain management ordinance, the elevation of the building's "lowest floor" as defined by the ordinance is: feet NGVD (or other FIRM datum-see Section B, Item 7). 2. Date of the start of construction or substantial improvement

## SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1-A30, AE, AH, A (with BFE), V1-V30, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features - If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.



